



Bowers & Wilkins

HTM6 S3

Technical Information



Technical features

Decoupled Double Dome Titanium tweeter
Continuum™ cone bass / midrange
Flowport™

Description

2-way vented-box system

Drive units

1x ø25mm (1 in) Titanium Dome high-frequency
2x ø130mm (5 in) Continuum cone bass / midrange

Frequency range

-6dB 42Hz - 33kHz

Frequency response

(+/-3dB from reference axis)

72Hz - 28kHz ±3dB

Sensitivity

(on axis at 2.83Vrms at 1m)

87dB

Harmonic distortion

2nd and 3rd harmonics (90dB, 1m on axis)
<1% 100Hz - 22kHz
<0.5% 120Hz - 12kHz

Nominal impedance

8Ω (minimum 4.3Ω)

Recommended amplifier power

30W - 120W into 8Ω on unclipped programme

Max. recommended cable impedance

0.1Ω

Dimensions

Height: 160 mm (6.3 in) cabinet only

Width: 480 mm (18.9 in) cabinet only

Depth: 255 mm (10 in) cabinet only
283 mm (11.2 in) including grille and terminals

Net weight

7.7kg (17.0lbs)

Finishes

Cabinet: Black
White
Oak

Grille: Black (Black)
Grey (White and Oak)